


Booster medium pressure

Medium Pressure Boosters are pump units providing an extra boost to the cleaning process



Nilfisk FOOD Hybrid Medium pressure range is a compact modular water supply system with 2 to 6 frequency controlled pumps to supply satellites for rinsing, foam cleaning and disinfection of exterior surfaces in the Food and Beverage industry.

The Hybrid Multi Booster range is built on a stainless steel floor frame and supplies satellites for simultaneous operation from 3 to 30 users.

It is to be used with the whole range of Hybrid satellites.

Standard models

Model	Article no.
Booster 40-3 w. frequency controlled pump/softstarter	119000631
Booster 40-6 w. frequency controlled pump/softstarter	119000628
Booster 40-10 w. frequency controlled pump/softstarter	119000630
Booster 40-20 w. MPC-E controller	119000149
Booster 40-30 w. MPC-E controller	119000068

Booster medium pressure

Medium Pressure Boosters - an extra boost to the cleaning process

Technical specifications

Water	BF40-3, BF40-6 & BF40-10	BF40-20 & BF40-30
Connection type inlet	BF40-3: ISO 228/1-G 1 1/4 BF40-6: ISO 228/1-G 1 1/2 BF40-10: SO 228/1-G 2	4" flange PN40 DIN2635
Connection type outlet Recommended	BF40-3: ISO 228/1-G 1 1/2 BF40-6: ISO 228/1-G 2 BF40-10: SO 228/1-G 2 1/2	4" flange PN40 DIN2635
Pump pressure	40 bar	40 bar
Adjustable operational pressure	40 bar + inlet pressure	40 bar + inlet pressure
Operational flow range	BF40-3: 120 l/min BF40-6: 240 l/min BF40-10: 400l/min	BF40-20: 800 l/min BF40-30: 1200 l/min
Min. inlet pressure	2 bar @ 120 l/min 2 bar @ 240 l/min 2 bar @ 400 l/min	2 bar @ 800 l/min 2 bar @ 1200 l/min
Max. inlet pressure	8 bar	8 bar
Max. water temperature	70°C	70°C
Electricity		
Power consumption	BF40-3: 11 kW BF40-6: 18,5 kW BF40-10: 33,5 kW	BF40-20: 67 kW BF40-30: 100,5 kW
Nom current	BF40-3: 21,3 A BF40-6: 32,4 A BF40-10: 65 A	BF40-20: 130 A BF40-30: 195 A
Security of electrical wiring	BF40-3: 35 A BF40-6: 63 A BF40-10: 80 A	BF40-20: 160 A BF40-30: 200 A
Electrical cable L1, L2, L3, PE	BF40-3: 4 x 2,5 mm2 BF40-6: 4 x 6,0 mm2 BF40-10: 4 x 16 mm2	BF40-20: 4 x 50 mm2 BF40-30: 4 x 95 mm2
General		
Number of pumps	BF40-4: 2 BF40-6: 2 BF40-10: 2	BF40-20: 4 BF40-30: 6
Sound level ISO 11202	Below 70dB	Below 70dB
Weight	BF40-3: 300 kg BF40-6: 350 kg BF40-10: 470 kg	BF40-20: 1100 kg BF40-30: 1450 kg
Dimensions HxWxD	BF40-3: 1600x420x1180mm BF40-6: 1490x420x1180mm BF40-10: 1770x500x1650mm	BF40-20: 1930x1800x-1470mm BF40-30: 1930x2500x-1470mm

Need more info?

Visit NILFISKFOOD.COM for more details including video tutorials and more.



Web



Video



Troubleshooting

Trust & Success - Already 4.500 worldwide installations at Costco, Carrefour, Safeway, Raley's, Weis, BJ's, Schnucks, PackNSave, Metro, Coop and many others...

Blytaekkervej 2
9000 Aalborg
Denmark

Nilfisk FOOD
NILFISKFOOD.COM

For further information:
Phone: +45 29 69 51 00
E-mail: info@nilfiskfood.com