

TECHNICAL SPECIFICATIONS

Water	230V/50 Hz	220V/60 HZ
Connection type inlet	ISO 228/1-G 3/4	ISO 228/1-G 3/4
Recommended inlet pipe dimensions (min)	3/4"	3/4"
Local outlet	1/2" quick coupler	1/2" quick coupler
Pump pressure	4 bar	5,7 bar
Operational pressure	6-10 bar	6-10 bar
Operational flow range	4-15 l/min	4-15 l/min
Min. inlet pressure	2 bar @ 15 l/min	2 bar @ 15 l/min
Max. inlet pressure	5 bar	4 bar
Max. water temperature	70°C	70°C
Electricity		
Power consumption	0,9 kW	1kW
Nom. current	5 A	8,7 A
Supply	1/PE 230Vac±10 50Hz	1/PE 220Vac±10 60Hz
Security of electrical wiring	12 A	12 A
Electrical cable; L1, L2, L3, PE	1,5 mm ²	1,5 mm ²
Nozzles (recommended)		
Rinsing nozzle	15/12	15/12
Foam nozzle	Foam lance 100 mm	Foam lance 100 mm
Spray nozzle	15/12	15/12

General		
Number of products	2	2
IP class	IP55	IP55
Max. hose length (recommended)	15 m (15 m)	15 m (15 m)
Sound level ISO 11202	Below 70 dB	Below 70 dB
Weight	31 kg	30 kg
Dimensions H x W x D	500 x 500 x 260 mm	50 x 500 x 260 mm

For technical specifications of other models available, see the Direction of use of the specific model in the Download section.

ISO 228/1-G 3/4

ISO 228/1-G 3/4