

TECHNICAL SPECIFICATIONS

Water	TW	HP	PD
Connection type inlet	ISO 228/1-G 1/2	ISO 228/1-G 1/2	ISO 228/1-G 1/2
Connection type outlet	ISO 228/1-G 1/2	ISO 228/1-G 1/2	ISO 228/1-G 1/2
Recommended inlet pipe dimension (min)	3/4" (1/2")	3/4" (1/2")	3/4" (1/2")
Water consumption - foaming	8,6 l/min @ 3 bar	7,8 l/min @ 40 bar	5,6 l/min @ 7 bar
Min. inlet pressure	3 bar	30 bar	6 bar
Max. inlet pressure	7 bar	80 bar	25 bar
Max. water temperature	70°C	70°C	70°C
Compressed air supply			
Connection type inlet	ø6 mm push in	ø6 mm push in	ø6 mm push in
Min. pressure of air supply	2 bar	6 bar	4 bar
Max. pressure of air supply	10 bar	10 bar	10 bar
Required flow rate	100 NI/min	200 NI/min	200 NI/min
Nozzles (recommended)			
Foam nozzle	50/200	50/200	50/200
General			
Number of products	1	1	1 (prediluted)

Max. hose length (recommended)	15 m	15 m	15 m
Weight	3 kg	3 kg	3 kg
Dimensions H x W x D	353 x 211 x 120 mm	353 x 211 x 120 mm	353 x 211 x 120 mm