

# TECHNICAL SPECIFICATIONS

## Water

Connection type inlet	ISO7/1-R1/2
Connection type outlet	1/2" quick coupler
Water consumption - foaming*	8,7 l/min@20 bar
Water consumption - spraying*	8,7 l/min@20 bar
Water consumption - rinsing	24,8 l/min@20 bar
Min. inlet pressure	12 bar
Max. inlet pressure	25 bar
Max. water temperature	70°C

## Pre-diluted detergent

Connection type inlet	ISO 228/1-F 1/2 Female
Min. inlet pressure prediluted products	6 bar
Max. inlet pressure prediluted products	10 bar
Prediluted products consumption	7.1 l/min@8 bar

## Compressed air supply

Connection type inlet	Ø6 push in
Min. pressure of air supply	6 bar
Max. pressure of air supply	10 bar
Required flow rate	200 NI/min

## Nozzles (recommended)

Rinsing nozzle	25/30
Foam nozzle	50/200
Spray nozzle	40/30

---

**General**

---

Number of products	2-4
--------------------	-----

---

Number of prediluted products	2-3
-------------------------------	-----

---

Max. hose length (recommended)	30 m (25m)
--------------------------------	------------

---

Sound level ISO 11202	Below 70dB
-----------------------	------------

---

Weight	7,5 kg
--------	--------

---

Dimensions H x W x D	530mm x 400mm x 140mm
----------------------	-----------------------

\* Local Pick up