## **GRIFF MOBILE**

Advanced cleaning and sanitizing station



Nilfisk FOOD Griff is a smart cleaning station with 8 bar/123 psi rinsing pressure and advanced foam technology to deliver superior soil removal in the food retail and institutional industry.

Advanced foam technology generated thanks to build in compressor delivers faster and more efficient cleaning.

Increased contact time of the detergents with the cleaned objects and the visible proof of cleaning delivers consistent cleaning results all over the plant and real economical savings.

According to an extensive field research results, Griff generates 22% of labour savings and 57% of water savings vs. traditional foamer.

Griff Mobile is intended to use as a single user cleaning and sanitizing station with three cleaning functions in one centrally located. The unit is mounted on a trolley giving additi-

### Applications

- Food retail: Fresh meat, fish & seafood, deli departments
- Modern institutional kitchens
- Food contact surfaces
- Food contact equipment
- Floors, Walls, Ceilings
- Hard to reach areas

### Features

- Unique Duo foam technology
- Two separate chemical products
  Three cleaning function in one
- centrally located selector switch
- Built in compressor
- Built in water pump
- Built in water check valve
- Wall mounted or trolley mounted

#### **Benefits**

- Superior soil removal
- Visible proof of cleaning
- Consistent cleaning results
- · Safe, easy and quick to operate
- · 23% labor cost savings\*
- 50% water cost savings\*

Nilfisk FOOD

Blytaekkervej 2 9000 Aalborg Denmark For further information: Phone: +45 29 69 51 00 E-mail: info@nilfiskfood.com

# **GRIFF MOBILE**

Advanced cleaning and sanitizing station

| General                                    | Unit            | 230V/50Hz               |                    | 220V/60Hz               |  |
|--|-----------------|-------------------------|--------------------|-------------------------|--|
| Number of products                         |                 | 2                       |                    | 2                       |  |
| Sound level                                | DB              | below 70                |                    | below 70                |  |
| Max. hose length recom.                    | М               | 15 (15)                 |                    | 15 (15)                 |  |
| Dimensions HxWxD                           | mm [inches]     | 1075x595x710 [42x23x28] |                    | 1075x595x710 [42x23x28] |  |
| Weight                                     | kg [lbs]        | 43 [94]                 |                    | 42 [92]                 |  |
| Water                                      |                 |                         |                    |                         |  |
| Operational flow range                     | L/min [gal/min] | 4-15 [1-3] /min         |                    | 4-15 [1-3] /min         |  |
| Operational pressure                       | MPa/bar [psi]   | 6-10 [87-145]           |                    | 6-10 [87-145]           |  |
| Min. supply pressure                       | MPa/bar [psi]   | 0.2/2 [29]              |                    | 0.2/2 [29]              |  |
| Max. supply pressure                       | MPa/bar [psi]   | 0.5/5 [72]              |                    | 0.5/5 [72]              |  |
| Max. water temperature                     | C° [F]          | 70 [158]                |                    | 70 [158]                |  |
| Electricity                                |                 |                         |                    |                         |  |
| Supply voltage                             | V               | 1/PE 230Vac +-50Hz      | 1/PE 220Vac +-60Hz |                         |  |
| Nominal current                            | А               | 5                       |                    | 8.7                     |  |
| Power consumption                          | kW              | 0.9                     |                    | 1                       |  |
| Electrical cable L1, L2, L3, PE            | mm2             | 1.5                     |                    | 1.5                     |  |
| Model                                      |                 |                         |                    | Article no              |  |
| Griff 230/50Hz                             |                 |                         |                    | 110003454               |  |
| Griff 220V/60Hz                            |                 |                         |                    | 110003519               |  |
| Griff 110V/60Hz                            |                 |                         |                    | 110006234               |  |
| Griff Accessory kit w/Super Nobel air hose |                 |                         |                    | 110006235               |  |
| Griff Accessory kit w/Purflex hose         |                 |                         |                    | 110003833               |  |



Need more info? Visit Nilfiskfood.com for more details including video tutorials and more.



Blytaekkervej 2 9000 Aalborg Denmark For further information: Phone: +45 29 69 51 00 E-mail: info@nilfiskfood.com