

Hybrid Typhoon Service Check List

Location	Description	Action	6 months	12 Months	18 Months	24 Months
1	Inlet filter	Inspect and clean inlet filter	X	X	X	X
2	Power lead and plug	Check condition of power lead and plug for cuts or damage, replace as required	X	X	X	X
3	User pack O-rings	Inspect condition of O-rings and suction seal	X	X	X	X
4	Quick Coupling O-rings	Replace		X		X
5	Selector switch Axel	Inspect O-rings/ Replace O-rings	X	X	X	X
6	Injectors	Clean, Inspect/ Replace O-rings	X		X	
		Replace		X		X
7	Air non return valve	Disassemble and Inspect/ Replace O-ring	X		X	
		Replace complete NRV		X		X
8	Chemical Non return valve	Disassemble, inspect/ replace O-ring	X		X	
		Replace complete NRV		X		X
9	Air valve	Inspect operation/ clean and lubricate piston	X		X	
		Replace if required		X		X
10	Flow switch	Inspect operation and adjust to 1 green light.	X	X	X	X
11	Water Check Valve	Disassemble, inspect/ replace O-ring and seat	X		X	
		Replace piston spring kit		X		X
12	Pressure switch	Check O-ring condition top of sensor and check display for, supply pressure, pump top pressure and temperature.	X	X	X	X
13	Air non return valve	Check operation	X		X	
		Replace complete NRV		X		X
	Faults read out	Inspect and record last 5 faults with dates.	X	X	X	X
	Chemical hoses	Replace chemical hoses		X		X

