

TECHNICAL SPECIFICATIONS

Hybrid Typhoon

Technical Data			
	Units	Hybrid Typhoon	Hybrid Typhoon 40
Water			
Max. outlet pressure	MPa (bar) [psi]	2.5(25) [36]	4.0 (40) [58]
Consumption during rinsing	L/min [gallon]	30 [7.9]	30 [7.9]
Consumption during foaming	L/min [gallon]	10 [2.6]	10 [2.6]
Min. supply pressure	MPa (bar) [psi]	0.2 (2) [29]	0.2 (2) [29]
Max. supply pressure	MPa (bar) [psi]	0.4 (4) [58]	0.4 (4) [58]
Min. water supply	L/min [gallon/min]	50 [13]	60 [15]
Max. water temperature	°C [°F]	70 [158]	70 [158]
Pipe dimension inlet Ø	inch	3/4"	3/4"
Compressed air (build in compressor)			
Air pressure	MPa (bar) [psi]	0.3-0.8 (3-8) [43.5-116]	0.3-0.8 (3-8) [43.5-116]
Compressed air consumption	NL/min	120	120
Electricity			
Supply voltage	V	3/PE 380-528VAC - 50/60Hz	
Frequency	Hz	50/60	50
Motor load (kW)	kW	2.2	7.5
Nominal current	A	7.7	15.2
Fuse	A	16	25
L1, L2, L3, PE	mm2	1.5	1.5
General			
Sound level ISO 11202	dB	below 71	below 71
Dimension HxWxD	mm [inches]	690x1445x1030 [27 x 56 x 40]	690x1445x1030 [27 x 56 x 40]
Weight	kg [lbs]	120 [264]	140 [308]