

# TECHNICAL SPECIFICATIONS

	<b>MultiFoamer Inox 200-15</b>	<b>MultiFoamer Inox 200-20</b>
<b>Water</b>		
Pipe dimension inlet Ø	Clamp Ø38	Clamp Ø 38
Pipe dimension outlet Ø	Clamp Ø38	Clamp Ø 38
Max. water consumption during foaming	10-32 l/min (2,6-8,5 gpm)	10-32 l/min (2,6-8,5 gpm)
Max. water consumption during rinsing	200 l/min (52,8 gpm)	200 l/min (52,8 gpm)
Min. pressure of water supply	2 bar	2 bar
Max. pressure of water supply	8 bar	8 bar
Max. temperature of water supply	70°C/158°F	70°C/158°F
Pipe dimension inlet/outlet Ø	38/38 mm	38/38 mm
<b>Compressed air supply</b>		
Air capacity	6-10 bar (87-145 psi) 200-450N l/min (52,8-118,8 gpm)	6-10 bar (87-145 psi) 200-450N l/min (52,8-118,8 gpm)
Pipe dimension air inlet	1/4"	
Min. pressure of air supply	87 psi	
Max. pressure of air supply	145 psi	
<b>Electricity</b>		
Power consumption	7,5 kW	7,5 kW
Nom. current	14,1 A	14,1 A
Security of electrical wiring	20A	20A
Electrical cable; L1, L2, L3, PE	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup>
<b>General</b>		
Number of products		
Construction		
IP class	IP55	