


# CERBERUS/DOORWAY

Censor controlled sanitation system for Doorway traffic in the Food & Beverage industry



Nilfisk FOOD Cerberus/Doorway sanitation system is a hygienic stainless steel wall mounted sanitation unit, operating via a nozzle system in floor height.

The nozzle system sprays out a pre-mixed solution of water and detergent/disinfection across a doorway at a pre-set interval. The water and detergent is mixed into a high quality foam which clings to e.g. boots and machinery wheels crossing the doorway.

Due to a very easily operated programming module/timer, it is possible, on-site, and in short time, to preset the time and intervals of the foam disinfection to accommodate your facility's particular traffic patterns.

The programming module/timer secures an automatic, steady and reliable foam disinfection performance.

## Applications

- Doorways

## Features

- Timer function incl. day/night program
- Prepared for level switch in chemical can / chemical dry run
- Prepared for switch from door (open/close)
- Prepared for signal from photocell
- Regulation of air (foam quality)
- Pre-mixed solution of water and detergent/disinfection

## Benefits

- Timer function incl. day/night program
- Prepared for level switch in chemical can / chemical dry run
- Prepared for switch from door (open/close)
- Prepared for signal from photocell
- Regulation of air (foam quality)
- Pre-mixed solution of water and detergent/disinfection

# CERBERUS/DOORWAY

Censor controlled sanitation system for Doorway traffic in the Food & Beverage industry

General	Unit	Cerberus Doorway
Number of products		1
Sound level	DB	below 70
Dimensions HxWxD	mm [inches]	380x460x190 [14x18x7]
Weight	kg [lbs]	9 [20]
IP class		66

Water		
Connection type inlet		½ quick coupler
Connection type outlet		½ quick coupler
Operational flow range	MPa (bar)[psi]	0.3 - 0.7 (3-7) [43-101]
Water consumption foam	L/min [gallon]	3-5 [0.8-1.3]
Min. inlet pressure	MPa (bar)[psi]@L[gallon]/min	0.3 (3) [43] @ 10 [2.6]
Max. inlet pressure	MPa (bar)[psi]	0.7 (7) [101]
Max. water temperature	°C [F]	70 [158]

Electricity		
Supply voltage	V	230
Nominal current	A	10
Fuse	A	10
Electrical cable L1, L2, L3, PE	mm2	3 x 1.5

Model	Article no	EBS no
SC Cerberus/Doorway sanitation System	110003423	10033215



**Need more info?** Visit [Nilfiskfood.com](https://www.nilfiskfood.com) for more details including video tutorials and more.