



MOBYFOAM

Mobile foam units for
small production areas

- ▲ Ergonomically designed trolleys
- ▲ Easily manoeuvrable
- ▲ Integrated hose rack
- ▲ Pneumatic operation
- ▲ Easy operation and maintenance



The **MOBYFOAM** mobile foam units, with a tank capacity of 113, 75 and 37 litres, offer innovative and ergonomic solutions for the cleaning of small areas in the food processing industry.

The easy manoeuvrable trolleys are equipped with an air operated diaphragm pump to generate the foam.

The tanks containing the cleaning solution are not pressurized, thus enabling additional filling during operation. The units are practically maintenance-free and easy to operate by means of single adjustment control for compressed air.

Features



Technical Data	FI-30N	FI-20N	FI-10N
EBS no.:	10018875	10014631	10014620
Air pressure (pump):	max. 5,5 bar	max. 5,5 bar	max. 5,5 bar
Air consumption:	140 - 280 NI/min	140 - 280 NI/min	140 - 280 NI/min
Foam output:	75 - 170 l/min	75 - 170 l/min	57 - 114 l/min
Capacity tank:	30 gallons, 113 litres	20 gallons, 75 litres	100 gallons, 37 litres
Water temperature:	max. 40 °C	max. 40 °C	max. 40 °C
Material trolley:	Polyethylene	Polyethylene	Polyethylene
Material pump:	Santoprene®	Santoprene®	Santoprene®
Hose length/diameter:	10 m/19 mm ID	10 m/19 mm ID	6 m/13 mm ID
Approvals:	CE	CE	CE
Dimensions (W x D x H):	43 x 79 x 94 cm	43 x 56 x 120 cm	40 x 48 x 104 cm
Weight (empty):	27 kg	23 kg	18 kg

EMEA Headquarters

Ecolab Europe GmbH
 Richtistrasse 7
 8304 Wallisellen
 Switzerland
 Tel. +41 44 877 2000

www.ecolab.com

