


TYPHOON MOBILE

Complete mobile hygiene station for open plant cleaning



Nilfisk FOOD Hybrid Typhoon is equipped with the new DuoBlock which allows 2 detergents, 1 of which could be mixed.

The mobile design allows reaching and cleaning every corner of your food premises despite the hose length.

The Hybrid Typhoon has an integrated water pump supplying a water pressure of 20 bars + inlet pressure, max 25 bar.

It has a built-in security kit with dry-run protection and automatic turn-off after 30 min. inactivity.

Applications

- Open plant surfaces

Features

- Corona technology
Better mix of air, detergent and water - generates approx. 20% more foam.
- DuoFoam Technology
The new injector block has the capacity for two different compounds at only one outlet, which makes it very easy and safe to change from one product to another.
- MIX, Double Injection Technology
The unique system is prepared for the injection of an extra booster product into the DuoFoamTechnology block, which takes the cleaning effect into a whole new level.

Benefits

- Flexible
- Safe
- Hygienic
- Saved time
- Saved labour costs
- Saved water costs

TYPHOON MOBILE

Complete mobile hygiene station for open plant cleaning

General	Unit	Hybrid Typhoon	Hybrid Typhoon 40
Number of products		2	2
Sound level	DB	below 71	below 71
Max. hose length recom.	M	25	25
Dimensions HxWxD	mm [inches]	690x1445x1030 [27x56x40]	690x1445x1030 [27x56x40]
Weight	kg [lbs]	120 [264]	140 [308]
IP class		55	55

Water			
Max. outlet pressure	MPa (bar)[psi]	2.5 (25)[362]	4.0 (40)[580]
Consumption during rinsing	L/min [gallon]	30 [7.9]	30 [7.9]
Consumption during foaming	L/min [gallon]	10 [2.6]	10 [2.6]
Min. supply pressure	MPa (bar)[psi]	0.2(2)[29]	0.2(2)[29]
Max. supply pressure	MPa (bar)[psi]	0.4(4)[58]	0.4(4)[58]
Min. water supply	L/min [gallon]	50 [13]	60 [15]
Max. water temperature	°C [F]	70 [158]	70 [158]
Pipe dimension inlet Ø	inch	3/4"	3/4"

Electricity			
Supply voltage	V	3/PE 380-528VAC-50/60Hz	
Nominal current	A	7.7	15.2
Motor load	kW	2.2	7.5
Fuse	A	16	25
Electrical cable L1, L2, L3, PE	mm ²	1.5	1.5

Model	Article no	EBS no
Hybrid Typhoon 50Hz	110004506	10036330
Hybrid Typhoon 50Hz, user pack	110004507	10036332
Hybrid Typhoon 50Hz, 40 bar	110004508	10036342
Hybrid Typhoon w/user pack, 40 bar	110004509	10036344
Hybrid Typhoon 60Hz	110004514	-
Hybrid Typhoon 60Hz, user pack	110004515	-



Need more info? Visit [Nilfiskfood.com](https://www.nilfiskfood.com) for more details including video tutorials and more.

Nilfisk FOOD
nilfiskfood.com

Blytaekervej 2
9000 Aalborg
Denmark

For further information:
Phone: +45 29 69 51 00
E-mail: info@nilfiskfood.com