

Extensions for Hybrid Foamatic

With the introduction of Hybrid Foamatic, we have also introduced new slave units. Each Hybrid Foamatic unit can have a maximum of two slaves.

It is important to order the correct slave(s) because they will have a different software from the standard PLC in the units.

A standard Hybrid Foamatic for 2x chemicals has 19 inputs and 10 outputs available.
A standard Hybrid Foamatic for 3x chemicals has 19 inputs and 9 outputs available.

Should you request more inputs and/or outputs, you must order the following:

MA units

1st slave for additional 20 inputs and 15 outputs – item no. 110005397

2nd slave for additional 20 inputs and 15 outputs – item no. 110005398

SA units

1st slave for additional 20 inputs and 15 outputs – item no. 110005734

2nd slave for additional 20 inputs and 15 outputs – item no. 110005398

A description on how and where to connect the slave(s) will be added to the manual, and a How-To-Video will be added to our website www.nilfiskfood.com.

Should you have any questions, please do not hesitate to contact us.



Nilfisk FOOD

Blytaekervej 2
9000 Aalborg
Denmark

For further information:

Phone: +45 29 69 51 00
E-mail: info@nilfiskfood.com

Want to change how you receive these emails?
You can [update your preferences](#) or [unsubscribe from this list](#).

Copyright © 2017 Nilfisk Food, All rights reserved.